

CLAIMS

1. Motor vehicle (1) with a roof (2), which has at least one part (3) that is fully movable to allow the roof to be opened, that extends from an area adjacent to a windshield frame (4) to a rear, especially rigid, roof part (5), that occupies the entire width in the transverse direction of the roof between the upper edges of the side windows (7) of the motor vehicle (1), and that comprises a foldable linkage that includes lateral frame parts (10; 11), characterized by the fact that the movable roof part (3), together with its linkage, can be folded and in its completely open position, can be lowered completely above the rear roof part (5), which has remained unmoved compared to its closed position.

2. Motor vehicle (1) with a roof (2), which has at least one part (3) that is fully movable to allow the roof to be opened and that extends from an area adjacent to a windshield frame (4) to a rear, especially rigid, roof part (5), especially in accordance with Claim 1, characterized by the fact that in its completely open position, the movable roof part (3) can be lowered optionally above or below the rear roof part (5).

3. Motor vehicle in accordance with Claim 1 or Claim 2, characterized by the fact that the movable roof part (3) has a textile covering.

4. Motor vehicle in accordance with any of Claims 1 to 3, characterized by the fact that the rear roof part (5) is in the same position in each fully opened position of the movable roof part (3) and in the fully closed position of the movable roof part (3).

5. Motor vehicle in accordance with any of Claims 1 to 4, characterized by the fact that the rear roof part (5) can be lowered below a belt line (31) of the automobile body.

6. Motor vehicle in accordance with any of Claims 1 to 5, characterized by the fact that the rear roof part (5) covers a rigid roll bar (32).

7. Motor vehicle in accordance with any of Claims 2 to 6, characterized by the fact that the rear roof part (5) is at least partially movable to create an opening for the passage of the movable roof part (3) to allow the latter to be lowered below the rear roof part (5).

8. Motor vehicle in accordance with Claim 7, characterized by the fact that the rear roof part (5) can be swung open at least partially about a rear axis (33) to create an opening for the passage of the roof part (3) and can be swung closed again over the lowered roof part (3).

9. Motor vehicle in accordance with any of Claims 1 to 8, characterized by the fact that the rear section (27) of the movable part (3) can be raised while the roof part (3) remains

otherwise closed.

10. Motor vehicle in accordance with Claim 9, characterized by the fact that the rear section (27) can be moved into and out of its raised position while the vehicle is traveling.

11. Motor vehicle in accordance with Claim 9 or 10, characterized by the fact that to allow the rear section to be raised, a roof bow (27) is provided which grips beneath the rear section and is displaceably mounted on lateral frame parts (11) of the movable roof part (3).